



1. XN755

Swivel Self Locking Hook / Brass Bushing

Part Code	Size (mm)	Weight (kg)	WLL (T)	A	B	E	E1	L1	L
XN755-06	6	0.71	1.12	32.5	24	30	28	152.5	184
XN755-07/8	7/8	1.15	2	36	29.5	28.9	35.8	189	228
XN755-10	10	1.86	3.15	42	35	48	48	224	270
XN755-13	13	3.51	5.3	50	41	54	52.5	267	324
XN755-16	16	7.33	8	61	56.8	47.5	63.3	355.6	406
XN755-20	18/20	10.3	12.5	72	63	52	86	378	460
XN755-22	22	17.5	15	97	98	60	76	466	564
XN755-26	26	23	21.2	123	115	97.3	96	544	661
XN755-32	32	81	31.5	140	146	99	135	679	829

- EN1677-3.
- Safety Factor 4:1

2. XN042

Swivel Self Locking Hook / Roller Bearing

Part Code	Size (mm)	Weight (kg)	WLL (T)	A	C	L1	L	T	E	M
XN042-06	6	0.71	1.12	32.5	33.8	160	194	28	32	70
XN042-07/8	7/8	1.1	2	36	40	202	240	35	39	88
XN042-10	10	2.0	3.15	42	48	237	283	45	48	108
XN042-13	13	4.0	5.3	50	58	282	343	52.5	65	134
XN042-16	16	7.3	8	61	60	341.5	419	63.3	65	168.6
XN042-20	18/20	11.6	12.5	76	75.5	399.5	483	86	85	186.2
XN042-22	22	16.0	15	97	97	466	564	76	80	202
XN042-26	26	21.5	21.2	123	115	544	661	96	125	244

- EN1677-3.
- Rotates under load.
- Safety Factor 4:1

- Fatigue Rated x 1.5 WLL for 20,000 cycles
- 100% Magnaflux Crack Detected
- Proof Tested - 2.5 times Working Load Limit
- Super Alloy Steel