



1. XN074 Connecting Link

Part Code	Size (mm)	Weight (kg)	WLL (T)	A	B	L	K	H
XN074-06	06	0.08	1.12	15	7.5	58	42	7
XN074-07/8	7/8	0.145	2	18	9.5	79.5	60.5	8.5
XN074-10	10	0.30	3.15	25	12	90.5	68	11.5
XN074-13	13	0.7	5.3	29	15	117	87	15
XN074-16	16	1.3	8	34.5	19.8	148	108.4	19.8
XN074-20	18/20	2.1	12.5	41	24	169.5	121.5	24
XN074-22	22	3.2	15	48	26	193.5	141.5	26
XN074-26	26	4.5	21.2	57.5	31	220	158	30
XN074-32	32	9	31.5	67	38	281	205	37

- EN1677-1.
- Safety Factor 4:1

2. XN002 Omega Link

Part Code	Size (mm)	Weight (kg)	WLL (T)	A	B	Ø	H	L
XN002-06	06	0.12	1.12	8	41	20.5	25	52
XN002-07/8	7/8	0.22	2.0	10	52	23.5	35	68.5
XN002-10	10	0.36	3.15	12	62	31.5	40.5	81
XN002-13	13	0.71	5.3	15	81	41	54	108
XN002-16	16	1.3	8	19	99	49.5	64	126
XN002-20	18/20	2.2	12.5	23	118	58	75.6	152

- EN1677-1.
- Safety Factor 4:1

- Fatigue Rated x 1.5 WLL for 20,000 cycles
- Super Alloy Steel
- Proof Tested - 2.5 times Working Load Limit
- All Load Pins are 100% individually inspected and tested
- 100% Magnaflux Crack Detected