



## 1. XN086 Clevis Grab Hook

| Part Code  | Size (mm) | Weight (kg) | WLL (T) | E    | A    | H    | W    | L     |
|------------|-----------|-------------|---------|------|------|------|------|-------|
| XN086-06   | 6         | 0.25        | 1.12    | 8    | 7.5  | 18   | 21.5 | 77    |
| XN086-07/8 | 7/8       | 0.32        | 2       | 10.5 | 9.5  | 21   | 33.5 | 89    |
| XN086-10   | 10        | 0.73        | 3.15    | 13   | 12.5 | 29   | 46   | 126   |
| XN086-13   | 13        | 1.6         | 5.3     | 16.5 | 15   | 42.5 | 57.5 | 163.5 |
| XN086-16   | 16        | 2.8         | 8       | 19   | 18.5 | 45.5 | 74   | 183.5 |
| XN086-20   | 18/20     | 5           | 12.5    | 24   | 23   | 56   | 74   | 219   |
| XN086-22   | 22        | 6.3         | 15      | 27   | 27   | 68.5 | 90   | 254   |
| XN086-26   | 26        | 14.5        | 21.2    | 30   | 30   | 77   | 102  | 309   |

- EN1677-1.
- Safety Factor 4:1

## 2. XN313 Clevis Grab Hook with Safety Pin

| Part Code  | Size (mm) | Weight (kg) | WLL (T) | A    | B    | E    | M     | L     |
|------------|-----------|-------------|---------|------|------|------|-------|-------|
| XN313-06   | 6         | 0.28        | 1.12    | 8    | 32   | 8    | 43.5  | 75    |
| XN313-07/8 | 7/8       | 0.33        | 2       | 9.5  | 35   | 11   | 49.5  | 89    |
| XN313-10   | 10        | 0.88        | 3.15    | 12.5 | 42.5 | 13.2 | 70.5  | 126.5 |
| XN313-13   | 13        | 1.85        | 5.3     | 15   | 53   | 16.5 | 90    | 163.5 |
| XN313-16   | 16        | 3.24        | 8       | 19.5 | 65.5 | 19.2 | 112.5 | 183.5 |

- EN1677-1.
- Safety Factor 4:1

- Fatigue Rated x 1.5 WLL for 20,000 cycles
- Proof Tested - 2.5 times Working Load Limit
- 100% Magnaflux Crack Detected
- Super Alloy Steel
- All Load Pins are 100% individually inspected and tested