

XN001 Web Sling Connector


Part Code	Size (mm)	Weight (kg)	WLL (T)	A	B	K	W	G	E
XN001-06	06	0.2	1.12	15	60	56	40	18	7
XN001-07/8	7/8	0.3	2.0	20	61.5	63.7	40	24	8.5
XN001-10	10	0.5	3.15	24	66	83	39	30.5	11
XN001-13	13	1.47	5.3	28	88	93.7	55	36.8	16.5
XN001-16	16	2.3	8	34.5	108	120	65.5	45.2	19.8
XN001-20	20	3.3	12.5	41	129	138	80	51.8	23
XN001-22	22	6.89	15	50	191	180	126	70	26
XN001-26	26	10.62	21.2	58	228.4	209.5	152	86	30
XN001-32	32	18.92	31.5	72.5	252	279	160	91	37

- EN1677-1.
- Safety Factor 4:1

XN235 Webbing Sling Link

- Safety Factor 4:1

Part Code	Size	Weight (kg)	WLL (T)	B.L/T	A	B	W	L
XN235-01	3.15T	0.23	3.15	12.6	12	41	61	76



- Fatigue Rated x 1.5 WLL for 20,000 cycles
- Proof Tested - 2.5 times Working Load Limit
- 100% Magnaflux Crack Detected
- Super Alloy Steel
- All Load Pins are 100% individually inspected and tested